


ETICHETTA INDELEBILE PER RIFERIMENTO UNICO



DATI TECNICI - TECHNICAL DATA

SCALA RANGE:	-35+35°C
DIFFERENZIALE / DIFFERENTIAL:	3 ± 2°C
TOLL. VALORI F.S.	± 3°C
CAPILLARE / CAPILLARY:	MM 1500 ACCIAIO INOX / INOX STEEL
INVOLUCRO MANOPOLA / CASE:	LIGHT BLUE PANTONE 2995C
SERIGRAFIA / DIAL:	RED KNOB - WHITE NUMBERS
PORTATA CONTATTI / BREAKING CAPACITY:	C1 15(2,5)A 400VAC / C2 2,5(0,4)A 400 VAC
MINIMUM CORRENT:	200 mA
INSULATION RESISTANCE:	> 100 M ohm
TEST DI VITA / LIFE OF PRODUCT:	100.000 CICLI / CYCLES
MAX °C SOPP. CORPO / MAX °C CASE	80°C
GRADO TENUTA / IP GRADE:	IP 40

MODIFICA	DOC.RIF.	DATA	APPARECCHIO ASSIEME PARTICOLARE	ARTH093	MATERIALE	TRATTAMENTO	DISEGNATO A. SALA	APPROVATO SALA A.	DATA
1			ARTH093				A. SALA	SALA A.	10/05/2016
2							SCALA		
3							1: 1		
4									
5									

ARTERHO