



SCHEMA ELETTRICO / ELECTRIC DIAGRAM
S.P.D.T.



DATI TECNICI - TECHNICAL DATA - SAFETY THERMOSTAT

SAFETY °C:	100°C ± 5°C
DIFFERENZIALE / DIFFERENTIAL:	
TOLL. VALORI F.S.	
POCKET:	BRASS 1/2" G
INVOLUCRO MANOPOLA / CASE:	LIGHT BLUE PANTONE 2995C
SERIGRAFIA / DIAL:	RED KNOB - WHITE NUMBERS
PORTATA CONTATTI / BREAKING CAPACITY:	C11 A 250 VAC - C2 16 A 250 VAC
MINIMUM CORRENT:	200 mA
INSULATION RESISTANCE:	>100 M ohm
TEST DI VITA / LIFE OF PRODUCT:	6.000 CICLI / CYCLES
MAX °C SOPP. CORPO / MAX °C CASE	70°C
GRADO TENUTA / IP GRADE:	IP 40

MODIFICA

DOC RIF. DATA

APPARECCHIO ASSIEME

PARTICOLARE

ARTH202



DESIGNATO A. SALA

APPROVATO SALA A.

SCALA 1:1

DATA 26/09/2013

NOTE

CODICE

ARTH202