



DATI TECNICI - TECHNICAL DATA

SCALA RANGE:	0/90°C
DIFFERENZIALE / DIFFERENTIAL:	4 ± 2,5°C
TOLL. VALORI F.S.	± 3°C
CAPILLARE / CAPILLARY:	POZZETTO G 1/2" / POCKET G 1/2"
INVOLUCRO MANOPOLA / CASE:	GREY ABS
SERIGRAFIA / DIAL:	GREY ABS - BLACK NUMBERS
PORTATA CONTATTI / BREAKING CAPACITY:	C1 15(2,5)A 400 VAC - C2 2,5(0,4)A 400 VAC
MINIMUM CORRENT:	200 mA
INSULATION RESISTANCE:	> 100 M ohm
TEST DI VITA / LIFE OF PRODUCT:	100.000 CICLI / CYCLES
MAX °C SOPP. CORPO / MAX °C CASE	70°C
GRADO TENUTA / IP GRADE:	IP 4.0

MODIFICA	DOC.RIF.	DATA	APPARECCHIO ASSIEME PARTICOLARE	ARTH100	MATERIALE	TRATTAMENTO	DATA	APPROVATO
1			ARTH100				A. SALA	SALA A.
2							SCALA	
3							1: 1	
4								
5								

ARTHERMO

DISEGNATO A. SALA

APPROVATO SALA A.
11/11/2011

ARTC-100