



DATI TECNICI - TECHNICAL DATA

SCALA RANGE:	0/90°C
DIFFERENZIALE / DIFFERENTIAL:	4 ± 2,5°C
TOLL. VALORI F.S.	± 3°C
CAPILLARE / CAPILLARY:	INOX CAPILLARY
INVOLUCRO / MANOPOLA / CASE:	GREY ABS
SERIGRAFIA / DIAL:	GREY KNOB - BLACK NUMBERS
PORTATA CONTATTI / BREAKING CAPACITY:	C1 15(2,5)A 400 VAC - C2 2,5(0,4)A 400 VAC
MINIMUM CORRENT:	200 mA
INSULATION RESISTANCE:	>100 M ohm
TEST DI VITA / LIFE OF PRODUCT:	100.000 CICLI / CYCLES
MAX °C SOPP. CORPO / MAX °C CASE	70°C
GRADO TENUITA / IP GRADE:	IP 40

MODIFICA

DOC.RIF. DATA

APPARECCHIO ASSIEME

PARTICOLARE ARTC-300

MATERIALE

TRATTAMENTO

NOTE

ARTERHO

DESIGNATO A. SALA

SCALA 1:1

APPROVATO SALA A.

DATA 18/01/2014

CODICE

ARTC-300

5