



ETICHETTA INDELEBILE PER RIFERIMENTO UNICO



SCHEMA ELETTRICO / ELECTRIC DIAGRAM  
S.P.D.T.



DATI TECNICI - TECHNICAL DATA

SCALA RANGE:	0/90°C
DIFFERENZIALE / DIFFERENTIAL:	4 ± 2.5°C
TOLL. VALORI F.S.	± 3°C
CAPILLARE / CAPILLARY:	POZZETTO G 1/2" / POCKET G 1/2"
INVOLUCRO MANOPOLA / CASE:	LIGHT BLUE PANTONE 2995C
SERIGRAFIA / DIAL:	RED KNOB - WHITE NUMBERS
PORTATA CONTATTI / BREAKING CAPACITY:	C1 15(2,5)A 400 VAC - C2 2,5(0,4)A 400 VAC
MINIMUM CORRENT:	200 mA
INSULATION RESISTANCE:	> 100 M ohm
TEST DI VITA / LIFE OF PRODUCT:	100.000 CICLI / CYCLES
MAX °C SOPP. CORPO / MAX °C CASE	80°C
GRADO TENUTA / IP GRADE:	IP 40

MODIFICA

DOC.RIF. DATA

APPARECCHIO ASSIEME

PARTICOLARE ARTH100

MATERIALE

TRATTAMENTO



DESIGNATO A. SALA  
SCALA 1:1

APPROVATO SALA A.  
DATA 11/11/2011

NOTE

CODICE

ARTH100