



DATI TECNICI - TECHNICAL DATA - SAFETY THERMOSTAT	
SAFETY °C :	100°C ± 5°C
DIFFERENZIALE / DIFFERENTIAL :	.
TOLL VALORI F.S.	.
CAPILLARE / CAPILLARY :	INOX CAPILLARY
INVOLUCRO / MANOPOLA / CASE :	LIGHT BLUE PANTONE 2995C
SERIGRAFIA / DIAL :	RED KNOB - WHITE NUMBERS
PORTATA CONTATTI / BREAKING CAPACITY :	C11 A 250 VAC - C2 16 A 250 VAC
MINIMUM CORRENT :	200 mA
INSULATION RESISTANCE :	> 100 M ohm
TEST DI VITA / LIFE OF PRODUCT :	6.000 CICLI / CYCLES
MAX °C SOPP. CORPO / MAX °C CASE :	70°C
GRADO TENUTA / IP GRADE :	IP 4.0

MODIFICA	DOC.RIF.	DATA	APPARECCHIO ASSIEME PARTICOLARE	ARTH201	DISIGNATO A. SALA	APPROVATO SALA A.
1			ARTH201			
2			MATERIALE		SCALA 1 : 1	DATA 26/09/2013
3			TRATTAMENTO			
4			NOTE			
5						



ARTH201