


| DATI TECNICI - TECHNICAL DATA - ADJUSTABLE THERMOSTAT | |
|-------------------------------------------------------|------------------------------------------|
| SCALA RANGE: | 0/90°C |
| DIFFERENZIALE / DIFFERENTIAL: | 4 ± 2,5°C |
| TOLL. VALORI F.S. | ± 3°C |
| POCKET: | COPPER / BRASS 1/2" G |
| INVOLUCRO MANOPOLA / CASE: | GREY |
| SERIGRAFIA / DIAL: | GREY KNOB / BLACK WRITING |
| PORTATA CONTATTI / BREAKING CAPACITY: | C1 15(2,5)A 400VAC / C2 2,5(0,4)A 400VAC |
| MINIMUM CORRENT: | 200 mA |
| INSULATION RESISTANCE: | >100 M ohm |
| TEST DI VITA / LIFE OF PRODUCT: | 100.000 CICLI / CYCLES |
| MAX °C SOPP. CORPO / MAX °C CASE | 70°C |
| GRADO TENUTA / IP GRADE: | IP 40 |

| DATI TECNICI - TECHNICAL DATA - THERMOMETER | |
|---------------------------------------------|------------------------------------------|
| SCALA / RANGE: | 0 /120 °C |
| QUADRANTE / DIAL: | WHITE DIAL/ BLACK NUMBERS - LOGO ARTERHO |
| RISOLUZIONE / RESOLUTION: | 2 °C |
| TRASPARENTE / TRANSPARENT: | PLASTIC TRANSPARENT |
| INDICE / POINTER: | BLACK PALSTIC |
| TARATURA / CALIBRATION: | 60 °C |
| CONTROLLO / CALIBRATION CHECK: | 100 °C +/- 2°C |
| CORPO / CASE: | BLACK PLASTIC |
| CORNICE / FRAME: | / |

SCHEMA ELETTRICO / ELECTRIC DIAGRAM
ADJUSTABLE THERMOSTAT



| MODIFICA | DOC.RIF. | DATA | APPARECCHIO ASSIEME PARTICOLARE | ARTHERMO |
|----------|----------|------|---------------------------------|----------|
| 1 | | | MULTI402 | |
| 2 | | | MATERIALE | |
| 3 | | | TRATTAMENTO | |
| 4 | | | NOTE | |
| 5 | | | | |

| | |
|-------------------|-------------------|
| DISIGNATO A. SALA | APPROVATO SALA A. |
| SCALA 1:1 | DATA 23/03/2015 |
| CODICE MULTI402 | |