


DATI TECNICI - TECHNICAL DATA - SAFETY THERMOSTAT	
SAFETY °C :	100°C ± 5°C
DIFFERENZIALE / DIFFERENTIAL :	.
TOLL. VALORI F.S. :	.
POCKET :	COPPER / BRASS 1/2" G
INVOLUCRO MANOPOLA / CASE :	LIGHT BLUE PANTONE 2995C
SERIGRAFIA / DIAL :	RED KNOB - WHITE NUMBERS
PORTATA CONTATTI / BREAKING CAPACITY :	C1 1A 250 VAC - C2 16A 250 VAC
MINIMUM CORRENT. :	200 mA
INSULATION RESISTANCE :	>100 M ohm
TEST DI VITA / LIFE OF PRODUCT :	6.000 Cycles
MAX °C SOPP. CORPO / MAX °C CASE :	70°C
GRADO TENUTA / IP GRADE :	IP 40

DATI TECNICI - TECHNICAL DATA - THERMOMETER	
SCALA / RANGE :	0 /120 °C
QUADRANTE / DIAL :	WHITE DIAL/ BLACK NUMBERS - LOGO ARTERHO
RISOLUZIONE / RESOLUTION :	2 °C
TRASPARENTE / TRANSPARENT :	PLASTIC TRANSPARENT
INDICE / POINTER :	BLACK PALSTIC
TARATURA / CALIBRATION :	60 °C
CONTROLLO / CALIBRATION CHECK :	100 °C +/- 2°C
CORPO / CASE :	BLACK PLASTIC
CORNICE / FRAME :	/

SCHEMA ELETTRICO / ELECTRIC DIAGRAM
SAFETY THERMOSTAT - S.P.D.T.



MODIFICA	DOC.RIF.	DATA	APPARECCHIO ASSIEME PARTICOLARE	ARTHERMO
1			MULTI403	
2			MATERIALE	
3			TRATTAMENTO	
4			NOTE	
5				

DISIGNATO A. SALA	APPROVATO SALA A.
SCALA 1:1	DATA 23/03/2015
CODICE MULT403	