



DATI TECNICI - TECHNICAL DATA

SCALA RANGE:	-35+35°C
DIFFERENZIALE / DIFFERENTIAL:	3 ± 2°C
TOLL. VALORI F.S.	± 3°C
CAPILLARE / CAPILLARY:	MM 1500 ACCIAIO INOX / INOX STEEL
INVOLUCRO MANOPOLA / CASE:	ABS GRIGIO / ABS GREY
SERIGRAFIA:	NUMERI NERI / BLACK NUMBERS
PORTATA CONTATTI / BREAKING CAPACITY:	C1 2,5(0,4) A 400VAC / C2 15(2,5) A 400VAC
MINIMUM CORRENT:	200 mA
INSULATION RESISTANCE:	> 100 M ohm
TEST DI VITA / LIFE OF PRODUCT:	100.000 CICLI / CYCLES
MAX °C SOPP. CORPO / MAX °C CASE	70°C
GRADO TENUTA / IP GRADE:	IP 44

MODIFICA

DOC.RIF. DATA

APPARECCHIO ASSIEME

PARTECOLARE

MATERIALE

TRATTAMENTO

NOTE

ARTHERMO

DISEGNATO A. SALA
SCALA 1:1

APPROVATO P. LAMBERTINI
DATA 03/04/2008

CODICE

TSC-093C